

POWERS YOUR BUSINESS!

LPT 810



LPT 810

SPECIFICATIONS

MODEL	LPT 810 Ex2
Engine Model	497 TCIC BS-III CR
Power	92 KW (125 PS) @ 2400 rpm
Torque	400 Nm @ 1300-1600 rpm
Clutch Type	310 mm Dia, Single Plate Dry
Gearbox	GBS 550 Synchromesh, (6F + 1R)
Suspension	Front: Semi-elliptical Leaf Springs Rear: Semi-elliptical Leaf Springs
Tyres	7.50 x 16 - 16 PR
Steering Type	Hydraulic Power Assisted (17.8:1)
Brakes	Dual Circuit Full Air S-Cam Brake
TCD (m)	TCD to be 13.5 for 3800 wb TCD to 12.3 for 3400 wb
Ground Clearance (mm)	205
Max. Speed (km/h)	100 (80 with speed limiter)
Gradeability	29%

GVW (kg)	8720
FAW (kg)	3160
RAW (kg)	5560
Front Axle	Heavy Duty Forged I Beam, Reverse Elliot Type
Rear Axle	Single Reduction Hypoid Gears, Fully Floating Axle Shafts
Battery	12 V, 100 Ah
Fuel Tank Capacity (lt)	160
Emission	BSIII
Dimensions	
Load Body Variants	Cab, HD
WB (in mm)	3400 & 3800
Load Body Length HD (mm/ft)	14.3 ft for 3400 mm 16.6 ft for 3800 mm
Load Body Width (mm/ft)	2042 (6.7)

TATA AFRICA HOLDINGS (T) LTD
PLOT No - 1 & 2,Vingunguti,Nyerere Road
P.O.Box 40207, Dar es Salaam, Tanzania
Tel: +255 22 286 2258 / 286 5177
Mob:+255 748 566 600

Tata Motors reserves the right to change and vary the design, technical specifications at any time, without prior notice, as per the Company's policy of continuous product improvement. The illustrations may show accessories and items of optional equipment which are not part of standard specifications. Colours may vary slightly from those shown, owing to limitations of printing process.