

TATA INTRA V20



Walk-through
Cabin



Best-in-Class
Gradeability



Gear Shift Advisor
(First Time in SCVs)



Bigger Tyres for Better
Load-carrying Capability



Lower NVH Levels
in the SCV Range

INTRA V20

TECHNICAL SPECIFICATIONS



ENGINE

ENGINE CAPACITY

1396 cc

ENGINE POWER

70 HP @ 4000 RPM

MAX. TORQUE

140 Nm @ 1800-3000 RPM

MAX. SPEED

80 Kmph

MAX. GRADEABILITY AT RATED GVW

45%

DRIVELINE

GEARBOX

Manual, 5-Forward, 1-Reverse

CLUTCH

Single Plate, Dry Friction, Diaphragm Type

STEERING AND BRAKES

STEERING

Power Steering

FRONT BRAKES

Disc Brakes

REAR BRAKES

Drum Brakes

SUSPENSION

FRONT SUSPENSION

Semi-elliptical Leaf Spring

REAR SUSPENSION

Semi-elliptical Leaf Spring

DIMENSIONS

WHEELBASE

2250 mm

OVERALL LENGTH

4282 mm

OVERALL WIDTH

1639 mm

OVERALL HEIGHT

1918 mm

GROUND CLEARANCE

170 mm

LOAD BODY

Pickup Type, Hinged Rear Tailgate

L X W X H (IN M)

2.45 X 1.54 X 0.40

TURNING RADIUS

4750 mm

WEIGHT

GVW

2300 Kg

KERB WEIGHT

1200 Kg

TYRE

165 R14 LT 8PR (Tubeless)

FUEL TANK

35L



TATA TANZANIA

TATA AFRICA HOLDINGS (T) LTD

PLOT No - 1 & 2, Vingunguti, Nyerere Road, P.O. Box 40207, Dar es Salaam, Tanzania

Tel: +255 22 286 2258 / 286 5177 Mob: +255 748 566 600