

# **BORN YODHA**

A winning combination of performance, ruggedness and style that not only aids your business but leads it too.

### STRONG AGGREGATES



**ENGINE** The newly redesigned TATA 4 SPCR TCIC 4-CYLINDER 3.0 L engine with a capacity of 2956 cc is powered to perform.



**POWER** 86 HP power with 250 Nm Torque.



**SPEED** Unrivalled Speed.



LARGEST LOAD BODY Rated payload of 1250 kgs.



HIGHEST GROUND CLEARANCE With ground clearance of 210mm, it's the highest in the category.



TYRES The wide 16" (215/75 R) radial tyres of the Yodha ensure better safety.



#### 

Front: 6 Semi-Elliptical Leaf Springs + Anti-Roll bar Rear: Innovative Two-stage Semi-Elliptical Leaf Springs - 9 Leaves.

### SOPHISTICATED COMFORT



**FLAT BENCH SEAT** Accommodates 3 people comfortably, unlike any in the category.



**LOCKABLE GLOVE BOX** Keep your important documents safe.



TRIP METER WITH DUAL READING A unique feature that is ideal for Fleet Owners to keep track of the vehicle movement & routes taken during the journey.



**INTENSITY CONTROL CABIN LIGHT** Allows the driver to adjust the intensity of the cabin light, depending upon the surroundings outside.



**ADJUSTABLE ANTI-GLARE REAR VIEW MIRROR The** rear view mirror of the Yodha can be adjusted by the driver to reduce the glare from outside.



**WORLD-CLASS CABIN SPACE** Newly designed spaces for maximum comfort.

## FLUID PERFORMANCE



GREAT RESTART GRADEABILITY OF 22% Keep climbing them even after sudden stops on steep roads.

FASTER PICK-UP Enables faster trips.

**EFFECTIVE BRAKING** Ensures complete safety while driving.

### **BEST CARE**

- BEST-IN-CLASS WARRANTY Comes with the best-in-class warranty of 3 years or 3 lakh km\*.
- BEST-IN-CLASS SERVICE INTERVALS The 15,000 km oil change interval so you stay on-road longer while saving 1 EMI every year.
- 21 POINT LIFE TIME LUBRICATED POINTS Yodha has 21 Life Time Lubricated Points which means reduced maintenance cost and faster service.



**FEATURES** YODHA BS IV

**ENGINE** 

Tata 4SPCR TCIC 4-cylinder BS IV Type

Capacity 2956 cc

64 kW (85 HP) @ 3000 rpm Max. Output Max. Torque 250 Nm@ 1000-2000 rpm

Fuel Tank Capacity 45 L

**CLUTCH & TRANSMISSION** 

Single plate dry friction type 260 mm Dia Clutch

Gearbox GBS 76 - 5/4.1

Synchromesh 5 forward #everse

Power steering Steering

**SUSPENSION** 

6 Semi-Elliptical Leaf Springs Front

Innovative two-stage Semi-Elliptical Leaf Rear

Springs - 9 Leaves

Anti-roll bar Front

**BRAKES** 

Hydraulic, twin-pot Disc Brakes Front

Drum Brakes Rear

WHEELS & TYRES

215/75 R 16" Radial Tyre

Rim size 16-Inch

**OVERALL VEHICLE** DIMENSIONS (mm)

Width 1860 Length 5350 Height 1810 **Ground Clearance** 210

Wheel Base 3150

Internal Load Body (L x B) 2550 (8.4 ft) x 1750 (5.7 ft)

Turning Circle Radius 6250

WEIGHT (kg)

GVW 3100 Kerb Weight 1850 Payload 1250

**PERFORMANCE** 

Gradeability 30% Restart Gradeability 22%

Top Speed

Seating type Lay Flat Seat

**WARRANTY TERMS** 

3 years or 3 Lakh km (whichever is earlier) Warranty (on Driveline)

For more information contact:

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement

As per terms & conditions in the operator's service manual.









